


ROLAMENTO RADIAL ESFERA RIGIDA EM POLEGADA



Open type



With dust cover
on both sides
(2Z)



With dust cover
Contact sealed type
(2RS)

Main Dimensions(mm)				Model			Reference Weight(Kg)	
d	D	B	B ₁	Open type	Shielded type	Contact sealed type	Open type	Shielded type Contact sealed type
12.700	28.575	6.350	7.938	R8	R8-2Z	R8-2RS	0.0190	0.0210
15.875	34.925	7.144	8.731	R10	R10-2Z	R10-2RS	0.0300	0.0360
19.050	41.275	7.938	11.113	R12	R12-2Z	R12-2RS	0.0470	0.0630
19.050	44.450	9.525	-	R13	R13-2Z	R13-2RS	0.0680	0.0920
22.225	47.625	9.525	12.700	R14	R14-2Z	R14-2RS	0.0700	0.0970
25.400	50.800	9.525	12.700	R16	R16-2Z	R16-2RS	0.0850	0.0970
28.575	53.975	9.525	12.700	R18	R18-2Z	R18-2RS	0.0910	0.1220
31.750	57.150	9.525	12.700	R20	R20-2Z	R20-2RS	0.0960	0.1250
34.925	63.500	11.113	14.288	R22	R22-2Z	R22-2RS	0.1540	0.2090
38.100	66.675	11.113	14.288	R24	R24-2Z	R24-2RS	0.1720	0.2310
12.700	28.575	6.350	7.938	SSR8	SSR8-2Z	SSR8-2RS	0.0190	0.0210
15.875	34.925	7.144	8.731	SSR10	SSR10-2Z	SSR10-2RS	0.0300	0.0360
19.050	41.275	7.938	11.113	SSR12	SSR12-2Z	SSR12-2RS	0.0470	0.0630
19.050	44.450	9.525	-	SSR13	SSR13-2Z	SSR13-2RS	0.0680	0.0920
22.225	47.625	9.525	12.700	SSR14	SSR14-2Z	SSR14-2RS	0.0700	0.0970
25.400	50.800	9.525	12.700	SSR16	SSR16-2Z	SSR16-2RS	0.0850	0.0970
28.575	53.975	9.525	12.700	SSR18	SSR18-2Z	SSR18-2RS	0.0910	0.1220
31.750	57.150	9.525	12.700	SSR20	SSR20-2Z	SSR20-2RS	0.0960	0.1250
34.925	63.500	11.113	14.288	SSR22	SSR22-2Z	SSR22-2RS	0.1540	0.2090
38.100	66.675	11.113	14.288	SSR24	SSR24-2Z	SSR24-2RS	0.1720	0.2310